

品名的阅读方法 MODEL NO. CODING

电动机 Motor

ZDF3 - 25 H 30 L S - 100 - S - B
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

①	系列 Series	ZDF2: F2系列 ZDF3: F3系列 ZDF2: F2 Series ZDF3: F3 Series
②	出轴直径或孔径	Shaft diameter or bore diameter
③	出轴类型 (实心轴见附图)	The shaft type (Solid shaft attached)
	H: 空心轴 A: 实心轴	H: Hollow shaft A: Solid shaft
④	减速比 Reduction ratio	30:1
⑤	L: 左出轴 R: 右出轴 T: 双出轴 (中空轴省略)	L: Left axis R: Right out axis T: Double output shaft (Hollow shaft omitted)
⑥	缩框型箱体 (标准型省略)	Shrink box type box (Standard type omitted)
⑦	额定输出功率 Rated output power	100:100W
⑧	F2电源 Power supply	C (单相 Single-phase 220V50/60Hz)
		H (单相 Single-phase 220V/60Hz)
		A (单相 Single-phase 110V50/60Hz)
		E (单相 Single-phase 110V/60Hz)
	F3电源 Power supply	S (3PH-220V50/60Hz)
		S3 (3PH-380V50/60Hz)
		U (3PH-220/380V50/60Hz)
		U (3PH-220/380V50/60Hz)
⑨	附加装置 Attachment unit	B: 刹车 FF: 强制风扇 F: 风扇 T: 接线盒 B: Brake FF: Axial flow fan F: Fan T: Connection box

注：⑨中F、T只针对ZDF2产品，ZDF3默认自带风扇，接线盒。Note: Line ⑨ is only refer to ZDF2 series. ZDF3 is preinstalled with fan and terminal box.

订单需注明安装方向 Order to indicate the direction of installation

